Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-390-1595

## **Body Style:**

Straight shape, external coupling

## **Overall Length:**

1.290 inches

# **Overall Height:**

1.688 inches

## **Overall Width:**

1.688 inches

## Center To Center Distance Between Mounting Facilities Parallel To Height:

1.375 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

#### 1.375 inches

**Distance From Mounting Shoulder To Front Face:** 

#### 0.790 inches

#### **Mating End Quantity:**

1

## **Contact Position Arrangement Style:**

23-53 single mating end

## **Polarization Method:**

Keyway or multiple keyway

#### Insert Position In Deg:

110.0

#### Shell Type:

Solid

#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping

#### **Shell Material:**

Aluminum alloy

#### **Included Contact Quantity:**

53 single mating end single contact grouping

#### Included Contact Type:

Round pin single mating end single contact grouping

#### **Precious Material:**

Gold

#### Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

96906-ms27656 government standard

# Shelf Life:

N/a

Electrical Receptacle Connector - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-38999 spec.