

View Online at <https://aerobasegroup.com/nsn/5935-01-390-7167>

Body Style:

Angle shape, pcb type

Overall Length:

6.400 inches

Overall Height:

0.550 inches

Overall Width:

0.522 inches

Environmental Protection:

Pressure proof

Unthreaded Mounting Hole Diameter:

0.120 inches

Distance Between Mounting Facility Centers:

6.150 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

3 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Friction

Operating Temperature Rating:

Between -45.0 degrees celsius and 85.0 degrees celsius

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy 172 single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic polyphenylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, grade c, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping and mil-c-14550 military specification 3rd treatment response single mating end single contact grouping

Terminal Type:

Printed circuit single mating end single contact grouping

Contact Material Specification:

Og-c-530, temper half hard federal specification single material response single mating end single contact grouping

Guide Design And Location:

D shape socket left-hand at 12 oclock and d shape pin right-hand at 12 oclock

Insert Material Specification:

Astm d4067 assn standard single material response single mating end

Included Contact Quantity:

160 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.160 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.