## NSN 5935-01-391-2535

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-391-2535

| Body Style:   |
|---|
| Angle shape   |
| Overall Length:   |
| 1.260 inches  |
| Overall Height:   |
| 0.460 inches  |
| Overall Width:  |
| 1.300 inches  |
| Body Length:  |
| 1.260 inches  |
| Body Height:  |
| 0.360 inches  |
| Environmental Protection:   |
| Corrosion resistant and fungus resistant and humidity resistant and shock resistant and vibration proof |
| Unthreaded Mounting Hole Diameter:  |
| Between 0.093 inches and 0.105 inches   |
| Distance Between Mounting Facility Centers:   |
| 0.860 inches  |
| Mating End Quantity:  |
| 1   |
| Contact Position Arrangement Style:   |
| 2 rows of contacts non-inserted board single mating end   |
| Contact Removability:   |
| Nonremovable single mating end single contact grouping  |
| Contact Maximum Current Rating In Amps:   |
| 1.0 single mating end single contact grouping   |
| Contact Maximum Ac Voltage Rating In Volts:   |
| 300.0 single mating end single contact grouping   |
| Connector Locking Method:   |
| Latch   |
| Terminal Location:  |
| Side single mating end single contact grouping  |
| Contact Material:   |
| Copper alloy single mating end single contact grouping  |
| Contact Surface Treatment:  |
| Gold single mating end single contact grouping  |
| Insert Material:  |
| Plastic polyester single mating end and glass fiber single mating end                                   |
| Terminal Type:  |

**Included Contact Quantity:** 

10 single mating end single contact grouping

Printed circuit single mating end single contact grouping

## NSN 5935-01-391-2535

Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 2



| Included Contact Type:   |
|--|
| Square pin single mating end single contact grouping   |
| Precious Material And Location:  |
| Contact surfaces gold  |
| Precious Material And Weight:  |
| 0.010 gold grains, troy  |
| Precious Material:   |
| Gold   |
| Test Data Document:  |
| 81349-mil-c-83503 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Specification Data:  |
| 81349-mil-c-83503/24 government specification  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
|  |