## NSN 5935-01-391-3016

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-391-3016

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight type
Overall Length:
4.300 inches
Overall Height:
0.465 inches
Overall Width:
0.350 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
3.600 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
3 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Thread Size:
0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end
Terminal Type:
Printed circuit single mating end single contact grouping
Unable To Decede:

Unable To Decode:

Unable to decode and unable to decode

## NSN 5935-01-391-3016

Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
104 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Jackscrew type-female and location-right handandjackscrew type-female and location-left hand
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.104 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No