NSN 5935-01-391-3175

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-391-3175

Thread Class:
2a and 2b
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
1.231 inches
Overall Diameter:
1.945 inches
Environmental Protection:
Corrosion resistant and shock resistant and vibration resistant and humidity resistant and dustproof
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
25-35 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
135.0 and 170.0 and 200.0 and 310.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Thready Qty Per Inch (tpi):
28 and 8
Thread Size:
1.500 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:

Terminal Type:

Plastic single mating end

Crimp single mating end single contact grouping

NSN 5935-01-391-3175

A039b0

Electrical Plug Connector - Page 2 of 2



Included Contact Quantity:
128 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.128 gold grains, troy
Precious Material:
Gold
Special Test Features:
Connector supplied with high performance contacts
Test Data Document:
91349-mil-c-29600 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Un
Specification Data:
91349-mil-c-29600/12 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: