Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-391-9043

Thread Class: 2a Thread Direction: Right-hand Body Style: Straight shape threaded Overall Length: 0.940 inches Overall Diameter: 2.160 inches Distance From Mounting Shoulder To Front Face: Between 0.761 inches and 0.781 inches Mounting Facility Thickness: 0.125 inches Threaded Device Type: Mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: 24-61 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type: Solid
Thread Direction: Right-hand Body Style: Straight shape threaded Overall Length: 0.940 inches Overall Diameter: 2.160 inches Distance From Mounting Shoulder To Front Face: Between 0.761 inches and 0.781 inches Between 0.761 inches and 0.781 inches Mounting Facility Thickness: 0.125 inches Threaded Device Type: Mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: 24-61 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type:
Right-hand Right-hand Body Style: Straight shape threaded Overall Length: 0.940 inches Overall Diameter: 2.160 inches Distance From Mounting Shoulder To Front Face: Between 0.761 inches and 0.781 inches Mounting Facility Thickness: 0.125 inches Threaded Device Type: Mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: 24-61 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type:
Body Style: Straight shape threaded Overall Length: 0.940 inches Overall Diameter: 2.160 inches Distance From Mounting Shoulder To Front Face: Between 0.761 inches and 0.781 inches Mounting Facility Thickness: 0.125 inches Threaded Device Type: Mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: 24-61 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type:
Straight shape threaded Overall Length: 0.940 inches Overall Diameter: 2.160 inches Distance From Mounting Shoulder To Front Face: Between 0.761 inches and 0.781 inches Mounting Facility Thickness: 0.125 inches Threaded Device Type: Mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: 24-61 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0
Overall Length: 0.940 inches Overall Diameter: 2.160 inches Distance From Mounting Shoulder To Front Face: Between 0.761 inches and 0.781 inches Between 0.761 inches and 0.781 inches Mounting Facility Thickness: 0.125 inches Threaded Device Type: Mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: 24-61 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type:
0.940 inches Overall Diameter: 2.160 inches Distance From Mounting Shoulder To Front Face: Between 0.761 inches and 0.781 inches Mounting Facility Thickness: 0.125 inches Threaded Device Type: Mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: 24-61 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0
Overall Diameter: 2.160 inches Distance From Mounting Shoulder To Front Face: Between 0.761 inches and 0.781 inches Mounting Facility Thickness: 0.125 inches Threaded Device Type: Mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: 24-61 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type:
2.160 inches Distance From Mounting Shoulder To Front Face: Between 0.761 inches and 0.781 inches Mounting Facility Thickness: 0.125 inches Threaded Device Type: Mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: 24-61 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type:
Distance From Mounting Shoulder To Front Face: Between 0.761 inches and 0.781 inches Mounting Facility Thickness: 0.125 inches Threaded Device Type: Mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: 24-61 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type:
Between 0.761 inches and 0.781 inches Mounting Facility Thickness: 0.125 inches Threaded Device Type: Mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: 24-61 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type:
Mounting Facility Thickness: 0.125 inches Threaded Device Type: Mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: 24-61 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type:
0.125 inches Threaded Device Type: Mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: 24-61 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type:
Threaded Device Type: Mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: 24-61 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type:
Mounting bushing Mating End Quantity: 1 Contact Position Arrangement Style: 24-61 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type:
Mating End Quantity: 1 Contact Position Arrangement Style: 24-61 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type:
1 Contact Position Arrangement Style: 24-61 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type:
24-61 single mating end Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type:
Contact Removability: Nonremovable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type:
Nonremovable single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type:
Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type:
Keyway or multiple keyway Insert Position In Deg: 0.0 Shell Type:
Insert Position In Deg: 0.0 Shell Type:
0.0 Shell Type:
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
End Application:
Pacer dawn
Thready Qty Per Inch (tpi):
18
-
Thread Size:
Thread Size:
Thread Size: 1.625 inches
Thread Size: 1.625 inches Terminal Location:
Thread Size: 1.625 inches Terminal Location: Back single mating end single contact grouping
Thread Size: 1.625 inches Terminal Location: Back single mating end single contact grouping Contact Material:

NSN 5935-01-391-9043

Electrical Receptacle Connector - Page 2 of 2



Shell Material:

Steel

Included Contact Quantity:

61 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Included Contact Type:

Round pin single mating end single contact grouping

Special Features:

Similar to m83723/81h connectors except for special terminations

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0