## NSN 5935-01-391-9043

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-391-9043 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape threaded **Overall Length:** 0.940 inches **Overall Diameter:** 2.160 inches **Distance From Mounting Shoulder To Front Face:** Between 0.761 inches and 0.781 inches **Mounting Facility Thickness:** 0.125 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 24-61 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **End Application:** Pacer dawn Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.625 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** 

Copper alloy single mating end single contact grouping

**Terminal Type:** 

Printed circuit single mating end single contact grouping

## NSN 5935-01-391-9043

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Steel
Included Contact Quantity:
61 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/flat
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Similar to m83723/81h connectors except for special terminations
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0