Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-392-1732

#### **Body Style:**

Angle shape, pcb type

#### **Overall Length:**

4.530 inches

# **Overall Height:**

0.450 inches

**Overall Width:** 

0.415 inches

#### **Environmental Protection:**

Vibration resistant and shock resistant and salt water resistant and cold resistant and thermal shock resistant

## **Distance Between Mounting Facility Centers:**

4.360 inches

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

3 rows of contacts non-inserted board single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

## Contact Maximum Ac Voltage Rating In Volts:

600.0 single mating end single contact grouping

## **Operating Tempurature Rating:**

Between -55.0 degrees celsius and 125.0 degrees celsius

## **Terminal Location:**

Side single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping

#### **Insert Material:**

Plastic polyphenylene single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

## **Terminal Type:**

Printed circuit single mating end single contact grouping

## Insert Material Specification:

Mil-m-24519 military specification single material response single mating end

## **Included Contact Quantity:**

152 single mating end single contact grouping

# **Precious Material:**

Gold

Electrical Receptacle Connector - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.