## NSN 5935-01-392-6291

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-392-6291 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Right angle type **Overall Length:** 1.250 inches **Overall Height:** 0.620 inches **Body Width:** 0.270 inches **Body Height:** 0.230 inches **Distance Between Mounting Facility Centers:** 1.000 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 26 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Jackscrew Shell Type: Solid **Connector Locking Method:** Jackscrew-socket **Unable To Decode:** Unable to decode and unable to decode **Thread Size:** 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

# NSN 5935-01-392-6291

Electrical Receptacle Connector - Page 2 of 2



#### **Contact Surface Treatment Specification:**

Mil-g-45204, type ii military specification single treatment response single mating end single contact grouping

#### **Terminal Type:**

Printed circuit single mating end single contact grouping

## **Contact Material Specification:**

Qq-b-750 federal specification single material response single mating end single contact grouping

## **Shell Material:**

Plastic melamine

#### **Shell Material Specification:**

Mil-m-14, type gd1-30f military specification single material response

#### **Unable To Decode:**

Unable to decode and unable to decode

#### **Included Contact Quantity:**

26 single mating end single contact grouping

#### **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Special Features:**

Jackscrew type-female and location-left handandjackscrew type-male and location-right hand

## **Precious Material And Location:**

Contact surfaces gold

## **Precious Material And Weight:**

0.026 gold grains, troy

## **Precious Material:**

Gold

## **Supplementary Features:**

Mounting method - jackscrew and jacksocket

## **Thread Series Designator:**

Unc

## Shelf Life:

N/a

## **Unit Of Measure:**

#### **Demilitarization:**

No

## Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.