Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-392-7522

Body Style:

Right angle type

Overall Length:

3.095 inches

Overall Height:

0.758 inches

Body Width:

0.390 inches

Body Height:

0.558 inches

Environmental Protection:

Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant

Unthreaded Mounting Hole Diameter:

Between 0.124 inches and 0.130 inches

Distance Between Mounting Facility Centers:

Between 2.765 inches and 2.785 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Mating end

Connector Locking Method:

Friction

Operating Tempurature Rating:

Between -65.0 degrees celsius and 125.0 degrees celsius

Terminal Location:

Side single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping and solder single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic single mating end

Contact Surface Treatment Specification:

ntaat Matarial Spaaifiaation.

Mil-g-45204, type 2, grade c, class1 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping and mil-p-81728 military specification 1st treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment response single mating end single contact grouping and mil-c-14550 military specification 2nd treatment

Terminal Type:

Printed circuit single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification:

Mil-m-24519, type gpt-15f military specification all material responses single mating end

Included Contact Quantity:

36 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Brush pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces, mating end gold

Precious Material And Weight:

0.036 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-55302/168 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.