NSN 5935-01-393-0492

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-393-0492

| View Online at https://aerobasegroup.com/nsn/5935-01-393-0492 |
|---|
| Body Style: |
| Rectangular shape |
| Overall Length: |
| 0.725 inches |
| Overall Height: |
| 0.600 inches |
| Overall Width: |
| 0.098 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 1 row of contacts non-inserted board single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 2.0 single mating end single contact grouping |
| Contact Maximum Dc Voltage Rating In Volts: |
| 500.0 single mating end single contact grouping |
| Operating Tempurature Rating: |
| Between -67.0 degrees fahrenheit and 221.0 degrees fahrenheit |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy 770 single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and nickel single mating end single contact grouping |
| Contact Surface Treatment Specification: |
| Mil-g-45204, type 2, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal |
| specification 2nd treatment response single mating end single contact grouping |
| Terminal Type: |
| Printed circuit single mating end single contact grouping |
| Included Contact Quantity: |
| 7 single mating end single contact grouping |
| Precious Material And Location: |
| Plating gold |
| Precious Material: |
| Gold |
| Supplementary Features: |
| Uses 3435-5 keying plug |
| Shelf Life: |
| N/a |

__

Unit Of Measure:

NSN 5935-01-393-0492

Electrical Plug Connector - Page 2 of 2



| _ | | | | | | | | | | |
|----|---|---|---|---|---|-----|----|---|---|--|
| וו | 0 | m | ш | м | • | iza | 31 | ^ | n | |
| | | | | | | | | | | |

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.