Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-393-1378

### **Body Style:**

Rectangular shape, insulation piercing

## **Overall Length:**

Between 2.073 inches and 3.103 inches

## **Overall Height:**

1.030 inches

## **Overall Width:**

Between 0.479 inches and 0.509 inches

### **Environmental Protection:**

Corrosion resistant and humidity resistant and shock resistant and vibration resistant

### **Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.125 inches

#### Distance Between Mounting Facility Centers:

1.852 inches

#### Mating End Quantity:

1

## **Contact Position Arrangement Style:**

25 single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

#### **Polarization Method:**

Mating end

### **Connector Locking Method:**

Friction

## **Connector Cable Strain Relief Method:**

Bracket

### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

# **Insert Material:**

Plastic diallyl phthalate single mating end

# **Terminal Type:**

Insulation piercing single mating end single contact grouping

# Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end or mil-m-24519, ty gpt-30f or ty get-30f military

specification single material response single mating end

# Included Contact Quantity:

25 single mating end single contact grouping

# Included Contact Type:

Round pin single mating end single contact grouping



## Precious Material And Location:

Contact surfaces gold

**Precious Material And Weight:** 

0.025 gold grains, troy

Precious Material:

Gold

### Test Data Document:

81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-c-24308/28 government specification

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.