NSN 5935-01-393-7227

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-393-7227 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.200 inches **Overall Diameter:** 0.750 inches **Distance From Mounting Shoulder To Front Face:** 0.821 inches **Mounting Facility Thickness:** 0.250 inches **Threaded Device Type:** Coupling facility and mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Tnc single mating end **Contact Removability:** Removable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Internally threaded coupling nut **Thread Size:** 0.500 inches and 0.625 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic polytetrafluoroethylene single mating end **Terminal Type:** Pin jack single mating end single contact grouping **Shell Material:**

Stainless steel

Shell Surface Treatment:

Passivate

NSN 5935-01-393-7227

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Coaxial pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.001 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unf and unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A039b0