Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-393-7242

Thread Class:

2a and 2b

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Length:

1.050 inches

Overall Height:

0.712 inches

Overall Width:

0.250 inches

Distance Between Mounting Facility Centers:

0.850 inches

Threaded Device Type:

Coupling facility and mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Jackscrew

Connector Locking Method:

Jackscrew-socket

Thread Size:

0.086 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polyphenylene single mating end and glass single mating end

Terminal Type:

Pin single mating end single contact grouping

Unable To Decode:

Unable to decode and unable to decode

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity: 14 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping **Special Features:** Jackscrew type-female and location-left handandjackscrew type-female and location-right hand **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.014 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0