NSN 5935-01-393-7242

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-393-7242 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 1.050 inches **Overall Height:** 0.712 inches **Overall Width:** 0.250 inches **Distance Between Mounting Facility Centers:** 0.850 inches **Threaded Device Type:** Coupling facility and mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Polarization Method:** Jackscrew **Connector Locking Method:** Jackscrew-socket Thread Size: 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic polyphenylene single mating end and glass single mating end

Terminal Type:

Pin single mating end single contact grouping

Unable To Decode:

Unable to decode and unable to decode

NSN 5935-01-393-7242

No Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
14 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Jackscrew type-female and location-left handandjackscrew type-female and location-right hand
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.014 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:

Demilitarization: