NSN 5935-01-394-2054

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-394-2054

Body Style:
Straight shape
Overall Length:
0.954 inches
Overall Height:
3.110 inches
Overall Width:
2.000 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 2.778 inches and 2.788 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.432 inches and 1.442 inches
Distance From Mounting Shoulder To Front Face:
0.766 inches
Mating End Quantity:
2
Contact Position Arrangement Style:
57m all mating ends
Contact Removability:
Nonremovable all mating ends all contact groupings
Contact Maximum Current Rating In Amps:
7.5 all mating ends all contact groupings
Contact Maximum Ac Voltage Rating In Volts:
1500.0 all mating ends all contact groupings
Polarization Method:
3 polarization posts
Shell Type:
Solid
Connector Locking Method:
Friction
Operating Tempurature Rating:
Between -67.0 degrees fahrenheit and 257.0 degrees fahrenheit
Terminal Location:

Back all mating ends all contact groupings

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings

Insert Material:

Plastic melamine all mating ends or plastic phenolic all mating ends

NSN 5935-01-394-2054

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder well all mating ends all contact groupings
Guide Design And Location:
Hexagon shape male post left-hand at 6 oclock
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
57 all mating ends all contact groupings
Included Contact Type:
Round socket all mating ends all contact groupings
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.057 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0