Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-394-2054

Body Style:
Straight shape
Overall Length:
0.954 inches
Overall Height:
3.110 inches
Overall Width:
2.000 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 2.778 inches and 2.788 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 1.432 inches and 1.442 inches
Distance From Mounting Shoulder To Front Face:
0.766 inches
Mating End Quantity:
2
Contact Position Arrangement Style:
57m all mating ends
Contact Removability:
Nonremovable all mating ends all contact groupings
Contact Maximum Current Rating In Amps:
7.5 all mating ends all contact groupings
Contact Maximum Ac Voltage Rating In Volts:
1500.0 all mating ends all contact groupings
Polarization Method:
3 polarization posts
Shell Type:
Solid
Connector Locking Method:
Friction
Operating Tempurature Rating:
Between -67.0 degrees fahrenheit and 257.0 degrees fahrenheit
Terminal Location:
Back all mating ends all contact groupings
Contact Material:
Copper alloy all mating ends all contact groupings
Contact Surface Treatment:
Gold all mating ends all contact groupings
Insert Material:
Plastic melamine all mating ends or plastic phenolic all mating ends
. Action model in the and of provide provide an induity of do



**Terminal Type:** Solder well all mating ends all contact groupings **Guide Design And Location:** Hexagon shape male post left-hand at 6 oclock **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Included Contact Quantity:** 57 all mating ends all contact groupings Included Contact Type: Round socket all mating ends all contact groupings **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.057 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0