

View Online at <https://aerobasegroup.com/nsn/5935-01-394-4598>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Angle shape, pcb type

Overall Length:

Between 4.340 inches and 4.360 inches

Overall Height:

0.525 inches

Overall Width:

0.390 inches

Environmental Protection:

Vibration resistant and shock resistant and humidity resistant and corrosion resistant

Distance Between Mounting Facility Centers:

Between 4.090 inches and 4.110 inches

Threaded Device Type:

Mounting hole

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Removable single mating end 1st contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end 1st contact grouping

Connector Locking Method:

Friction

Thread Length:

0.224 inches

Operating Temperature Rating:

Between -55.0 degrees celsius and 125.0 degrees celsius

Features Provided:

Pre-tinned terminal

Thready Qty Per Inch (tpi):

40

Thread Size:

0.112 inches

Terminal Location:

Side single mating end 1st contact grouping

Contact Material:

Copper alloy single mating end 1st contact grouping

Contact Surface Treatment:

Gold single mating end 1st contact grouping and nickel single mating end 1st contact grouping

Insert Material:

Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type ii, class 1, grade c military specification 1st treatment response single mating end 1st contact grouping and qq-n-290 federal specification 2nd treatment response single mating end 1st contact grouping

Terminal Type:

Printed circuit single mating end 1st contact grouping

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end 1st contact grouping or qq-c-533 federal specification single material response single mating end 1st contact grouping or qq-b-750 federal specification single material response single mating end 1st contact grouping

Insert Material Specification:

Mil-m-14, type sgd-f or type gdi-30f military specification 1st material response single mating end or mil-m-24519, type gpt-30f or gst-40f military specification 2nd material response single mating end

Included Contact Quantity:

68 single mating end 1st contact grouping

Included Contact Type:

Round socket single mating end 1st contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.068 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Specification Data:

26916-010-006511 manufacturers specification control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.