NSN 5935-01-394-4662

Electrical Receptacle Connector - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5935-01-394-4662 |
|--|
| Body Style: |
| Straight type |
| Overall Length: |
| 2.295 inches |
| Overall Height: |
| 1.095 inches |
| Overall Width: |
| 0.590 inches |
| Unthreaded Mounting Hole Diameter: |
| Between 0.122 inches and 0.127 inches |
| Distance Between Mounting Facility Centers: |
| 1.975 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 4 rows of contacts non-inserted board single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Polarization Method: |
| Mating end |
| Connector Locking Method: |
| Friction |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Copper single mating end single contact grouping and lead single mating end single contact grouping and tin single mating end single |
| contact grouping |
| Terminal Type: |
| Printed circuit single mating end single contact grouping |
| Included Contact Quantity: |
| 40 single mating end single contact grouping |
| Included Contact Type: |
| Brush pin single mating end single contact grouping |
| Test Data Document: |
| 81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 81349-mil-c-55302/166 government specification |

N/a

Shelf Life:

Unit Of Measure:

NSN 5935-01-394-4662

Electrical Receptacle Connector - Page 2 of 2



Demilitarization:

No

Fiig:

A039b0