Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-394-4664

Body Sty	
Straight ty	
Overall L	
7.295 incl	-
Overall H	
1.095 incl	-
Overall V	
0.590 incl	
	led Mounting Hole Diameter:
	0.122 inches and 0.127 inches
	Between Mounting Facility Centers:
6.975 incl	
Mating E	nd Quantity:
1	
	Position Arrangement Style:
	contacts non-inserted board single mating end
	Removability:
	vable single mating end single contact grouping
	ion Method:
Mating en	nd
-	or Locking Method:
Friction	
Terminal	Location:
Back sing	le mating end single contact grouping
Contact I	Material:
Copper a	lloy single mating end single contact grouping
	Surface Treatment:
Copper si	ingle mating end single contact grouping and lead single mating end single contact grouping and tin single mating end single
contact gi	rouping
Terminal	Туре:
Printed ci	rcuit single mating end single contact grouping
Included	Contact Quantity:
240 single	e mating end single contact grouping
Included	Contact Type:
Brush pin	single mating end single contact grouping
Test Data	a Document:
81349-mi	I-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; e	xcludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environm	ental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
	ation Data:
81349-mi	I-c-55302/166 government specification
Shelf Life	2:
N/a	

Unit Of Measure:

Electrical Receptacle Connector - Page 2 of 2



Demilitarization:

No

Fiig:

A039b0