## NSN 5935-01-394-4667

Electrical Receptacle Connector - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5935-01-394-4667  |
|--|
| Body Style:  |
| Straight type  |
| Overall Length:  |
| 2.295 inches   |
| Overall Height:  |
| 0.840 inches   |
| Overall Width:   |
| 0.490 inches   |
| Unthreaded Mounting Hole Diameter:   |
| Between 0.122 inches and 0.127 inches  |
| Distance Between Mounting Facility Centers:  |
| 1.975 inches   |
| Mating End Quantity:   |
| 1  |
| Contact Position Arrangement Style:  |
| 3 rows of contacts non-inserted board single mating end  |
| Contact Removability:  |
| Nonremovable single mating end single contact grouping   |
| Polarization Method:   |
| Mating end   |
| Connector Locking Method:  |
| Friction   |
| Terminal Location:   |
| Back single mating end single contact grouping   |
| Contact Material:  |
| Copper alloy single mating end single contact grouping   |
| Contact Surface Treatment:   |
| Copper single mating end single contact grouping and lead single mating end single contact grouping and tin single mating end single         |
| contact grouping   |
| Terminal Type:   |
| Printed circuit single mating end single contact grouping  |
| Included Contact Quantity:   |
| 30 single mating end single contact grouping   |
| Included Contact Type:   |
| Brush pin single mating end single contact grouping  |
| Test Data Document:  |
| 81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Specification Data:  |
| 81349-mil-c-55302/166 government specification   |

Unit Of Measure:

Shelf Life:

N/a

## NSN 5935-01-394-4667

Electrical Receptacle Connector - Page 2 of 2



Demilitarization:

No

Fiig:

A039b0