NSN 5935-01-395-0036

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-395-0036

Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
1.836 inches
Overall Diameter:
0.686 inches
Cable Entrance Diameter:
0.205 inches
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
7-oct single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
165.0
Shell Type:
Shell Type: Solid
• •
Solid
Solid Connector Locking Method:
Solid Connector Locking Method: Bayonet latch
Solid Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method:
Solid Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Cable clamp
Solid Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Cable clamp Operating Tempurature Rating:
Solid Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Cable clamp Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius
Solid Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Cable clamp Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location:
Solid Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Cable clamp Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping
Solid Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Cable clamp Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material:
Solid Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Cable clamp Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:
Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Cable clamp Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Solid Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Cable clamp Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping
Solid Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Cable clamp Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material:
Solid Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Cable clamp Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Rubber single mating end
Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Cable clamp Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Rubber single mating end Terminal Type:
Connector Locking Method: Bayonet latch Connector Cable Strain Relief Method: Cable clamp Operating Tempurature Rating: Between -55.0 degrees celsius and 125.0 degrees celsius Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Rubber single mating end Terminal Type: Solder well single mating end single contact grouping

Cadmium and chromate

NSN 5935-01-395-0036

Electrical Plug Connector - Page 2 of 2



Included Contact Quantity:

7 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.007 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0