## NSN 5935-01-395-1531

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-395-1531 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, pcb, external coupling **Overall Length:** 0.525 inches **Overall Height:** 0.250 inches **Overall Width:** 0.250 inches **Distance From Mounting Shoulder To Front Face:** 0.215 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 335.0 single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 36 **Thread Size:** 0.250 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping

**Insert Material:** 

Plastic polytetrafluoroethylene single mating end

## NSN 5935-01-395-1531

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Printed circuit single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Gold
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Body gold and contact surface gold
Precious Material:
Gold
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0