Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-395-2481

Bodv	Style:

Rectangular shape

**Overall Length:** 

3.260 inches

# **Overall Height:**

1.495 inches

# **Overall Width:**

0.360 inches

#### **Unthreaded Mounting Hole Diameter:**

0.096 inches

### **Distance Between Mounting Facility Centers:**

3.100 inches

### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

#### Contact Removability:

Removable single mating end single contact grouping

### **Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

## **Polarization Method:**

Key or multiple key

## Shell Type:

Solid

### **Connector Locking Method:**

Bayonet latch

### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

### **Contact Surface Treatment Specification:**

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd

treatment response single mating end single contact grouping

### **Terminal Type:**

Crimp single mating end single contact grouping

#### **Contact Material Specification:**

Qq-b-750 federal specification single material response single mating end single contact grouping

#### **Shell Material:**

Plastic polyester

### **Included Contact Quantity:**

50 single mating end single contact grouping



Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

**Precious Material And Weight:** 

0.050 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.