NSN 5935-01-395-3733

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-395-3733

Thread Class:
2a and 2b
Thread Direction:
Right-hand
Body Style:
Hood, top opening w/clamp
Overall Length:
1.500 inches
Overall Height:
1.740 inches
Overall Width:
0.390 inches
Cable Entrance Diameter:
0.340 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
44 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Jackscrew
Shell Type:
Solid
Connector Locking Method:
Jackscrew-socket
Connector Cable Strain Relief Method:
Cable clamp
Thread Size:
0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate glass filled single mating end
Terminal Type:
Crimp single mating end single contact grouping

NSN 5935-01-395-3733Electrical Plug Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
44 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.044 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-28748/13 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unc
Specification Data:
8134928748/13 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0