NSN 5935-01-395-4977

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-395-4977

Thread Class:
2a and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Angle shape, external coupling
Overall Length:
0.707 inches
Overall Width:
0.478 inches
Mounting Hole Circle Radius:
0.387 inches
Overall Diameter:
0.500 inches
Threaded Device Type:
Mounting bushing and mounting hole
Mating End Quantity:
1
Contact Position Arrangement Style:
Smc single mating end
Contact Removability:
Removable single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Threaded hole
Thread Size:
0.190 inches and 0.073 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic fluorocarbon single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 1, grade c, class 2 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp and solder single mating end single contact grouping
Contact Material Specification:

Qq-b-626 federal specification single material response single mating end single contact grouping

NSN 5935-01-395-4977

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Copper alloy
Shell Surface Treatment:
Gold
Shell Material Specification:
Qq-b-626 federal specification single material response
Insert Material Specification:
L-p-403 federal specification single material response single mating end
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.001 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unf and unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.