## NSN 5935-01-396-1994



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-396-1994 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 4.990 inches **Overall Height:** 0.695 inches **Overall Width:** 0.576 inches **Distance Between Mounting Facility Centers: 4.700** inches **Threaded Device Type:** Mounting hole

**Mating End Quantity:** 

2

**Contact Removability:** 

Removable all mating ends all contact groupings

**Polarization Method:** 

Guide pin/socket

**Connector Locking Method:** 

Friction

**Thread Size:** 

0.086 inches

**Terminal Location:** 

Back all mating ends all contact groupings

**Contact Material:** 

Copper alloy all mating ends all contact groupings

**Contact Surface Treatment:** 

Gold all mating ends all contact groupings

**Insert Material:** 

Plastic polyamide single mating end

**Terminal Type:** 

Printed circuit all mating ends all contact groupings

**Unable To Decode:** 

Unable to decode and unable to decode

**Included Contact Quantity:** 

210 all mating ends all contact groupings

**Included Contact Type:** 

Flat pin all mating ends all contact groupings

## NSN 5935-01-396-1994

Electrical Receptacle Connector - Page 2 of 2



Special Features:
Double surface mount connector with 5 rows of contacts, 3mounting ears, 210 contacts.
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.210 gold grains, troy
Precious Material:
Gold
Supplementary Features:
Mounting method - threaded hole
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A039b0