## NSN 5935-01-396-2958

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-396-2958

Thread Direction:
Right-hand
Body Style:
Right angle type
Overall Length:
175.5 millimeters
Overall Width:
9.4 millimeters
Distance Between Mounting Facility Centers:
167.6 millimeters
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Connector Locking Method:
Friction
Thread Size:
2.5 millimeters
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Pin single mating end single contact grouping
Insert Material Specification:
Mil-m-14 military specification single material response single mating end
Thread Tolerance Class:
6g external

**Included Contact Quantity:** 

120 single mating end single contact grouping

## NSN 5935-01-396-2958

Mil-m-14 spec.

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:	
Round pin single mating end single contact grouping	
Precious Material And Location:	
Contact surfaces gold	
Precious Material And Weight:	
0.120 gold grains, troy	
Precious Material:	
Gold	
Test Data Document:	
81349-dod-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification	tion
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Thread Series Designator:	
Iso s	
Specification Data:	
81349-dod-c-55302/163 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Standard):	