

View Online at <https://aerobasegroup.com/nsn/5935-01-396-2960>

Body Style:

Straight shape, panel solder

Overall Length:

2.000 inches

Overall Diameter:

0.650 inches

Environmental Protection:

Salt spray proof and vibration resistant and thermal shock resistant and shock resistant and moisture resistant

Mating End Quantity:

1

Contact Maximum Ac Voltage Rating In Volts:

400.0 single mating end single contact grouping

Connector Locking Method:

Friction

Operating Temperature Rating:

Between -65.0 degrees celsius and 165.0 degrees celsius

Terminal Location:

Front single mating end single contact grouping

Terminal Type:

Pin single mating end single contact grouping

Included Contact Quantity:

3 single mating end single contact grouping

Test Data Document:

81349-milc49142 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349--49142/08-0006 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-c-49142 spec.