## NSN 5935-01-396-4579

Electrical Receptacle Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-01-396-4579



**Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.875 inches **Cable Entrance Diameter:** 0.080 inches **Distance From Mounting Shoulder To Front Face:** 0.425 inches **Threaded Device Type:** Coupling facility and mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Smc single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell **Connector Cable Strain Relief Method:** Compression nut Width Across Flats: 0.250 inches **Thread Size:** 0.190 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic polytetrafluoroethylene single mating end **Terminal Type:** 

**Shell Material:**Copper alloy

Crimp single mating end single contact grouping

## NSN 5935-01-396-4579

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:	
Gold	
Included Contact Quantity:	
1 single mating end single contact grouping	
Bushing Accommodation Hole Shape:	
Round w/flat	
Included Contact Type:	
Coaxial socket single mating end single contact grouping	
Precious Material And Location:	
Contact surfaces gold and shell surfaces gold	
Precious Material And Weight:	
0.105 gold grains, troy	
Precious Material:	
Gold	
Thread Series Designator:	
Unf	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A039b0	