Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-396-4589

Body Style:
Straight type
Overall Length:
4.300 inches
Overall Height:
0.657 inches
Overall Width:
0.350 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
4.050 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
3 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Polarization Method: Jackscrew
Jackscrew
Jackscrew Connector Locking Method:
Jackscrew Connector Locking Method: Jackscrew-socket
Jackscrew Connector Locking Method: Jackscrew-socket Terminal Location:
Jackscrew Connector Locking Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping
Jackscrew Connector Locking Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Contact Material:
Jackscrew Connector Locking Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Contact Material:
Jackscrew Connector Locking Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:
Jackscrew Connector Locking Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping
Jackscrew Connector Locking Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material:
Jackscrew Connector Locking Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic polyphenylene single mating end
Jackscrew Connector Locking Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic polyphenylene single mating end Terminal Type:
Jackscrew Connector Locking Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic polyphenylene single mating end Terminal Type: Pin single mating end single contact grouping
Jackscrew Connector Locking Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic polyphenylene single mating end Ferminal Type: Pin single mating end single contact grouping Unable To Decode:
Jackscrew Connector Locking Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic polyphenylene single mating end Terminal Type: Pin single mating end single contact grouping Unable To Decode: Unable to decode and unable to decode
Jackscrew Connector Locking Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic polyphenylene single mating end Irerminal Type: Pin single mating end single contact grouping Unable To Decode: Unable to decode and unable to decode Included Contact Quantity:
Jackscrew Connector Locking Method: Jackscrew-socket Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic polyphenylene single mating end Terminal Type: Pin single mating end single contact grouping Unable To Decode: Included Contact Quantity: 104 single mating end single contact grouping

Jackscrew type-female and location-left handandjackscrew type-female and location-right hand



**Precious Material And Location:** 

Contact surfaces gold

Precious Material And Weight:

0.104 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0