Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-397-0949

## **Body Style:**

Straight shape

# **Overall Length:**

Between 2.620 inches and 2.650 inches

# **Overall Height:**

0.653 inches

## **Overall Width:**

Between 0.590 inches and 0.620 inches

### **Environmental Protection:**

Corrosion resistant and humidity resistant and shock resistant and vibration resistant

## **Unthreaded Mounting Hole Diameter:**

Between 0.115 inches and 0.125 inches

### Distance Between Mounting Facility Centers:

Between 2.401 inches and 2.411 inches

### Mating End Quantity:

Contact Position Arrangement Style:

78 single mating end

# **Contact Removability:**

Removable single mating end single contact grouping

## Polarization Method:

Mating end

Shell Type:

Solid

1

## **Connector Locking Method:**

Friction

## **Operating Tempurature Rating:**

Between -55.0 degrees celsius and 125.0 degrees celsius

## **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping

### **Insert Material:**

Plastic diallyl phthalate glass filled single mating end or plastic polyester glass filled single mating end

## **Terminal Type:**

Crimp single mating end single contact grouping

# Shell Material:

Metal

# Shell Surface Treatment:

Passivate



## **Included Contact Quantity:**

78 single mating end single contact grouping

## Included Contact Type:

Round socket single mating end single contact grouping

# **Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:** 

0.078 gold grains, troy

## **Precious Material:**

Gold

### **Test Data Document:**

81349-mil-c-24308 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

81349-mil-c-24308/6 government specification

Shelf Life:

N/a

---

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0