### NSN 5935-01-397-5552

Electrical Receptacle Connector - Page 1 of 2



| i e   |
|---|
| View Online at https://aerobasegroup.com/nsn/5935-01-397-5552 |
| Thread Class:   |
| 2a and 2b   |
| Thread Direction:   |
| Right-hand  |
| Body Style:   |
| Right angle type  |
| Overall Length:   |
| 3.650 inches  |
| Overall Width:  |
| 0.390 inches  |
| Body Height:  |
| 0.400 inches  |
| Threaded Device Type:   |
| Coupling facility   |
| Mating End Quantity:  |
| 1   |
| Contact Position Arrangement Style:                           |
| 2 rows of contacts non-inserted board single mating end       |
| Contact Removability:   |
| Nonremovable single mating end single contact grouping        |
| Contact Maximum Current Rating In Amps:                       |
| 5.0 single mating end single contact grouping                 |
| Polarization Method:  |
| Jackscrew   |
| Connector Locking Method:                                     |
| Jackscrew-socket  |
| Thread Size:  |
| 0.086 inches  |
| Terminal Location:  |
| Side single mating end single contact grouping                |
| Contact Material:   |
|   |

Copper alloy single mating end single contact grouping

## Contact Surface Treatment:

Gold single mating end single contact grouping

### Insert Material:

Plastic diallyl phthalate glass filled single mating end

#### **Terminal Type:**

Pin single mating end single contact grouping

#### Unable To Decode:

Unable to decode and unable to decode

#### **Included Contact Quantity:**

66 single mating end single contact grouping

# NSN 5935-01-397-5552

Electrical Receptacle Connector - Page 2 of 2



| Round pin single mating end single contact grouping  |
|--|
| Special Features:  |
| Jackscrew type-female and location-left handandjackscrew type-male and location-right hand |

**Precious Material And Location:** 

**Included Contact Type:** 

Contact surfaces gold

**Precious Material:** 

Gold

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

No

Fiig:

A039b0