Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-397-6427

# **Body Style:**

Straight shape, external coupling

### **Overall Diameter:**

Between 2.2960 inches and 2.3380 inches

### **Environmental Protection:**

Hermetic and humidity resistant and corrosion resistant and thermal shock resistant

# Distance From Mounting Shoulder To Front Face:

Between 0.910 inches and 0.920 inches

### Threaded Device Type:

Back shell

#### **Contact Position Arrangement Style:**

25-35 single mating end

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

# Insert Position In Deg:

0.0

#### Shell Type:

Solid

## **Connector Locking Method:**

Bayonet shell

## **Terminal Location:**

Back single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping

#### Shell Material:

Steel

## Shell Surface Treatment:

Tin

## **Included Contact Quantity:**

128 single mating end single contact grouping

#### Included Contact Type:

Round pin single mating end single contact grouping

## **Special Features:**

Item has special 'turned down' terminals and jam nut mounting dimensions.

# **Precious Material And Location:**

Contact surfaces gold

## **Precious Material And Weight:**

0.1280 gold grains, troy

### **Precious Material:**

Gold

Electrical Receptacle Connector - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0