## NSN 5935-01-398-6220

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-398-6220

**Body Style:** 

Straight shape, internal coupling

**Overall Length:** 

0.374 inches

**Overall Height:** 

0.500 inches

**Overall Width:** 

0.500 inches

**Environmental Protection:** 

Corrosion resistant and humidity resistant and moisture resistant and thermal shock resistant

**Unthreaded Mounting Hole Diameter:** 

0.102 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.340 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.340 inches

**Mating End Quantity:** 

....

**Contact Position Arrangement Style:** 

Sma single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

600.0 single mating end single contact grouping

Shell Type:

Solid

**Operating Tempurature Rating:** 

Between -65.0 degrees celsius and 105.0 degrees celsius

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Beryllium single mating end single contact grouping and copper single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Contact Surface Treatment Specification:** 

Mil-g-45204 mfr ref single treatment response single mating end single contact grouping

**Terminal Type:** 

Crimp single mating end single contact grouping

**Contact Material Specification:** 

Qq-c-530 mfr ref single material response single mating end single contact grouping

**Shell Material:** 

Stainless steel

## NSN 5935-01-398-6220

Electrical Receptacle Connector - Page 2 of 2



| Shell Surface Treatment:                                |
|---|
| Passivate   |
| Shell Surface Treatment Specification:                  |
| Qq-p-35 federal specification single treatment response |
| Shell Material Specification:                           |
| Qq-s-764 federal specification single material response |
| Included Contact Quantity:                              |
| 1 single mating end single contact grouping             |
| Included Contact Type:                                  |
| Round pin single mating end single contact grouping     |
| Precious Material And Location:                         |
| Contact surfaces gold                                   |
| Precious Material:                                      |
| Gold  |
| Supplementary Features:                                 |
| Mounting method - unthreaded hole                       |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:                                       |
| No  |
| Fiig:   |
| A039b0  |
| Mil-std (military Standard):                            |

Mil-g-45204 spec.