

NSN 5935-01-398-8252 Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-398-8252 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Rectangular shape **Overall Length:** 3.050 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.782 inches **Overall Height:** 1.163 inches **Overall Width:** 0.500 inches **Environmental Protection:** Corrosion resistant and humidity resistant Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.250 inches **Threaded Device Type:** Coupling facility and mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 100 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping

Polarization Method:

Guide pin/socket and jackscrew

Connector Locking Method:

Jackscrew

Operating Tempurature Rating:

Between 0.0 degrees celsius and 85.0 degrees celsius

Thready Qty Per Inch (tpi):

40

Thread Size:

0.112 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

NSN 5935-01-398-8252

Electrical Receptacle Connector - Page 2 of 2



| insert Material: |
|-------------------------------------------------------------------------------------------------------|
| Plastic diallyl phthalate single mating end |
| Terminal Type: |
| Wire wrap single mating end single contact grouping |
| Unable To Decode: |
| Unable to decode and unable to decode |
| Unable To Decode: |
| Unable to decode and unable to decode |
| Included Contact Quantity: |
| 100 single mating end single contact grouping |
| Included Contact Type: |
| Round pin single mating end single contact grouping |
| Special Features: |
| Jackscrew type-male and location-left hand bottomandjackscrew type-female and location-right hand top |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.100 gold grains, troy |
| Precious Material: |
| Gold |
| Supplementary Features: |
| Mounting method - stud |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| |
| |