## NSN 5935-01-399-2276

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-399-2276

view Online at https://aerobasegroup.com/nsn/5955-01-599-2276
Body Style:
Straight shape
Unable To Decode:
Unable to decode and unable to decode
Overall Length:
Between 2.055 inches and 2.065 inches
Overall Height:
0.942 inches
Overall Width:
0.600 inches
Unable To Decode:
Unable to decode and unable to decode
Unable To Decode:
Unable to decode and unable to decode
Distance Between Mounting Facility Centers:
Between 1.745 inches and 1.755 inches
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Inter-contact polarizing keys
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy 172 single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204 type 1, grade c, class 1 military specification single treatment response single mating end single contact grouping
Terminal Type:
Wire wrap single mating end single contact grouping
Contact Material Specification:
Qq-c-533 federal specification single material response single mating end single contact grouping
Shell Material:
Aluminum alloy

Cadmium

**Shell Surface Treatment:** 

## NSN 5935-01-399-2276

Electrical Receptacle Connector - Page 2 of 2



## **Shell Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response

**Shell Material Specification:** 

Qq-b-591 federal specification single material response

**Included Contact Type:** 

Round socket single mating end single contact grouping

**Special Features:** 

Furnished items - hardware kit and protective cover

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material:** 

Gold

Shelf Life:

N/a

Unit Of Measure:

--

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.