## NSN 5935-01-399-2537

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-399-2537

**Body Style:** 

Straight shape, internal coupling

Overall Length:

0.953 inches

**Overall Diameter:** 

1.031 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

13119 single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

100.0 and 128.0 and 228.0 and 265.0 and 328.0

**Shell Type:** 

Solid

**Connector Locking Method:** 

Bayonet slot

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic epoxy single mating end

**Terminal Type:** 

Crimp single mating end single contact grouping

**Shell Material:** 

Aluminum alloy

**Shell Surface Treatment:** 

Cadmium

**Included Contact Quantity:** 

22 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.022 gold grains, troy

## NSN 5935-01-399-2537

Electrical Plug Connector - Page 2 of 2



Gold
Test Data Document:
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
96906-ms27484 government standard
Shelf Life:
N/a
Unit Of Measure:
- <del>-</del>
Demilitarization:

A039b0

No **Fiig:** 

Mil-std (military Standard):

Mil-c-38999 spec.

**Precious Material:**