## NSN 5935-01-399-4924

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-399-4924

**Body Style:** 

Straight shape, flush mount

**Overall Length:** 

1.634 inches

**Overall Height:** 

Between 3.060 inches and 3.090 inches

Overall Width:

Between 1.985 inches and 2.015 inches

**Environmental Protection:** 

Humidity resistant and salt water resistant and shock resistant and thermal shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

Between 0.118 inches and 0.122 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

2.782 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.436 inches

**Distance From Mounting Shoulder To Front Face:** 

Between 0.055 inches and 0.065 inches

**Mating End Quantity:** 

1

**Polarization Method:** 

Mating end

Shell Type:

Solid

**Connector Locking Method:** 

Friction

**Terminal Location:** 

Back all mating ends single contact grouping

**Contact Material:** 

Copper alloy all mating ends single contact grouping

**Contact Surface Treatment:** 

Gold all mating ends single contact grouping

Insert Material:

Plastic diallyl phthalate glass filled all mating ends or plastic epoxy all mating ends or plastic phenolic all mating ends

**Terminal Type:** 

Crimp all mating ends single contact grouping

**Shell Material:** 

Aluminum alloy

**Shell Surface Treatment:** 

Cadmium and chromate

**Precious Material And Location:** 

Contact surfaces gold

## NSN 5935-01-399-4924

Electrical Receptacle Connector - Page 2 of 2



Precious Material:	P	rec	ious	Mate	rial:	
--------------------	---	-----	------	------	-------	--

Gold

## **Test Data Document:**

81349-mil-c-81659 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-c-81659/35 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0