## NSN 5935-01-400-1641

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-400-1641 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 33.16 millimeters **Overall Diameter:** 32.5 millimeters **Environmental Protection:** Moisture proof and salt water resistant and vibration proof and corrosion resistant and dust resistant and fuel resistant and fungus resistant and humidity resistant and oil resistant and shock resistant and thermal shock resistant and vibration resistant **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 15-35 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 53.0 and 156.0 and 220.0 and 255.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling ring **Thread Size:** 22.0 millimeters and 1.000 inches **Terminal Location:** Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping

#### **Terminal Type:**

Crimp single mating end single contact grouping

### **Shell Material:**

Aluminum alloy

#### **Shell Surface Treatment:**

Nickel

# **NSN 5935-01-400-1641**Electrical Plug Connector - Page 2 of 2



| Thread Tolerance Class:  |
|--|
| 6g external  |
| Included Contact Quantity:   |
| 37 single mating end single contact grouping   |
| Included Contact Type:   |
| Round pin single mating end single contact grouping  |
| Precious Material And Location:  |
| Contact surfaces gold  |
| Precious Material:   |
| Gold   |
| Test Data Document:  |
| 81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Thread Series Designator:  |
| lso m and special acme   |
| Specification Data:  |
| 81349-dod-c-38999/26 government specification  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <del></del>  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A039b0   |
|  |
|  |