Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-401-5307

## **Thread Class:** 2b **Thread Direction: Right-hand Body Style:** Angle shape, w/o cable clamp **Overall Diameter:** Between 1.990 inches and 2.010 inches **Body Angle In Deg:** 90.0 **Environmental Protection:** Pressure proof and thermal shock resistant and vibration resistant and shock resistant and humidity resistant and corrosion resistant **Threaded Device Type:** Coupling facility Mating End Quantity: 1 **Contact Position Arrangement Style:** 12 number 16 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Internally threaded coupling nut **Distance From Centerline To Connector End:** Between 3.450 inches and 3.750 inches **Distance From Centerline To Cable End:** 2.952 inches **Thread Size:** 1.750 inches **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:**

Plastic diallyl phthalate glass filled single mating end

## NSN 5935-01-401-5307

Electrical Plug Connector - Page 2 of 2



**Terminal Type:** Crimp single mating end single contact grouping Shell Material: Steel comp 316 **Shell Surface Treatment:** Passivate **Included Contact Quantity:** 12 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.012 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0