

View Online at <https://aerobasegroup.com/nsn/5935-01-406-2363>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

Between 1.019 inches and 1.079 inches

Overall Diameter:

0.500 inches

Unthreaded Mounting Hole Diameter:

0.140 inches

Distance From Mounting Shoulder To Front Face:

0.717 inches

Mounting Facility Thickness:

0.4375 inches

Threaded Device Type:

Mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

Bnc single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

750.0 single mating end single contact grouping

Connector Locking Method:

Bayonet pin

Thread Size:

0.437 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic polychlorotrifluoroethylene single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Nickel and cadmium

Shell Surface Treatment Specification:

Mil-p-27418 military specification 1st treatment response and qq-p-416 federal specification 2nd treatment response

Insert Material Specification:

Astm d-1710 assn standard single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/flat

Precious Material:

Gold

Supplementary Features:

Mounting method - bracket

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.