NSN 5935-01-406-3832

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-406-3832

Body Style:

Straight shape

Overall Length:

8.500 inches

Overall Height:

0.565 inches

Overall Width:

Between 0.510 inches and 0.530 inches

Unthreaded Mounting Hole Diameter:

Between 0.120 inches and 0.130 inches

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.0 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic polyphenylene single mating end and glass single mating end

Contact Surface Treatment Specification:

Mil-g-45204. Type ii, class 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290 federal specification 2nd treatment response single mating end single contact grouping and mil-c-14550 military specification 3rd treatment response single mating end single contact grouping

Terminal Type:

Printed circuit single mating end single contact grouping

Contact Material Specification:

Qq-b-626, alloy 360 federal specification single material response single mating end single contact grouping

Guide Design And Location:

V groove socket right-hand at 10: 30 oclock

Insert Material Specification:

Mil-m-24519, type gst-40f military specification all material responses single mating end

Included Contact Quantity:

279 single mating end single contact grouping

Included Contact Type:

Pound socket single mating and single contact grouping

NSN 5935-01-406-3832

Electrical Receptacle Connector - Page 2 of 2



| Precious Material And Location: |
|---------------------------------|
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.279 gold grains, troy |
| Precious Material: |
| Gold |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |

Mil-std (military Standard):

Mil-g-45204 spec.