## NSN 5935-01-406-7683

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-406-7683 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling w/backshell **Overall Length:** 2.125 inches **Overall Height:** 1.188 inches **Overall Width:** 1.188 inches **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.130 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.906 inches **Distance From Mounting Shoulder To Front Face:** 0.562 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 14s-7 single mating end **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:** Externally threaded shell **Thread Length:** 0.290 inches and 0.375 inches **Thread Size:** 0.875 inches and 0.875 inches **Insert Material:** Plastic silicone mineral filled single mating end

**Shell Material:** Aluminum alloy

## NSN 5935-01-406-7683

Mil-std (military Standard):

Mil-c-5015 spec.

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0