Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-406-7683

Thread Class:
2a and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, external coupling w/backshell
Overall Length:
2.125 inches
Overall Height:
1.188 inches
Overall Width:
1.188 inches
Unthreaded Mounting Hole Diameter:
Between 0.115 inches and 0.130 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.906 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.906 inches
Distance From Mounting Shoulder To Front Face:
0.562 inches
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
14s-7 single mating end
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Thread Length:
0.290 inches and 0.375 inches
Thread Size:
0.875 inches and 0.875 inches
Insert Material:
Plastic silicone mineral filled single mating end
Shell Material:
Aluminum alloy

NSN 5935-01-406-7683

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Thread Series Designator:

Unef and unef

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-5015 spec.