NSN 5935-01-407-8522

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-407-8522 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Straight type **Overall Length:** 2.650 inches **Overall Height:** 0.637 inches **Overall Width:** 0.250 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches **Distance Between Mounting Facility Centers:** 2.400 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Jackscrew **Connector Locking Method:** Jackscrew-socket **Thread Size:** 0.086 inches Copper alloy single mating end single contact grouping

Terminal Location: Back single mating end single contact grouping **Contact Material: Contact Surface Treatment:** Gold single mating end single contact grouping **Terminal Type:** Pin single mating end single contact grouping

Unable To Decode:

Unable to decode and unable to decode

NSN 5935-01-407-8522

Demilitarization:

No Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
36 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Jackscrew type-female and location-left handandjackscrew type-male and location-right hand
Precious Material And Location:
Contact surfaces gold
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure: