Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-407-9621

#### **Body Style:**

Angle shape, pcb, external coupling

**Overall Length:** 

0.385 inches

## **Overall Height:**

0.380 inches

## **Overall Width:**

0.156 inches

#### **Distance From Mounting Shoulder To Front Face:**

0.210 inches

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

Nonstd single mating end

### **Contact Maximum Current Rating In Amps:**

1.0 single mating end single contact grouping

### Contact Maximum Ac Voltage Rating In Volts:

250.0 single mating end single contact grouping

## **Contact Maximum Frequency Rating:**

12.0 gigahertz single mating end single contact grouping

#### Shell Type:

Solid

#### **Connector Locking Method:**

Friction

#### Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

#### **Terminal Location:**

Side single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping

## **Insert Material:**

Plastic polytetrafluoroethylene single mating end

# **Terminal Type:**

Pin single mating end single contact grouping

# Shell Material:

Copper alloy

## Shell Surface Treatment:

Gold

## **Included Contact Quantity:**

1 single mating end single contact grouping



Included Contact Type:

Coaxial pin single mating end single contact grouping

### **Precious Material And Location:**

Contact and body surfaces gold

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0