NSN 5935-01-408-0638

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-408-0638

| Body Style: |
|---|
| Straight type |
| Overall Length: |
| 8.295 inches |
| Overall Height: |
| 0.703 inches |
| Overall Width: |
| 0.590 inches |
| Environmental Protection: |
| Shock resistant and vibration resistant and corrosion resistant and humidity resistant and fungus resistant |
| Distance Between Mounting Facility Centers: |
| 7.795 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 4 rows of contacts non-inserted board single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Polarization Method: |
| Mating end |
| Connector Locking Method: |
| Friction |
| Operating Tempurature Rating: |
| Between -65.0 degrees celsius and 125.0 degrees celsius |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and nickel single mating end single contact grouping |
| Insert Material: |
| Glass fiber single mating end and plastic single mating end |
| Terminal Type: |
| Printed circuit single mating end single contact grouping |
| Included Contact Quantity: |
| 280 single mating end single contact grouping |
| Included Contact Type: |
| Brush pin single mating end single contact grouping |
| Special Features: |
| Following not supplied with connector: four m55302/78-02 polarizing keys: coupling/mounting bushings, m55302/172-01, and -02. |

Contact surfaces gold

Precious Material And Location:

NSN 5935-01-408-0638

Electrical Receptacle Connector - Page 2 of 2



| Precious | Material And | Weight: |
|----------|---------------------|----------|
| 1001040 | material / tila | TTOIGHT. |

0.280 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-55302 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-55302/166 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0