NSN 5935-01-408-1034

Electrical Plug Connector - Page 1 of 2



| view Online at https://aerobasegroup.com/nsn/5935-01-406-1034 |
|--------------------------------------------------------------------------------------------------------|
| Body Style: |
| Straight shape |
| Overall Length: |
| 0.398 inches |
| Overall Height: |
| 1.120 inches |
| Overall Width: |
| 0.098 inches |
| Environmental Protection: |
| Heat resistant and cold resistant and vibration resistant and shock resistant |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 1 row of contacts non-inserted board single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 3.0 single mating end single contact grouping |
| Connector Locking Method: |
| Spring friction |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping |
| Insert Material: |
| Plastic single mating end |
| Contact Surface Treatment Specification: |
| Mil-g-45204 military specification single treatment response single mating end single contact grouping |
| Terminal Type: |
| Crimp single mating end single contact grouping |
| Included Contact Quantity: |
| 4 single mating end single contact grouping |
| Included Contact Type: |
| Square socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.004 gold grains, troy |
| Precious Material: |

Gold

NSN 5935-01-408-1034

Electrical Plug Connector - Page 2 of 2



| N/a | |
|-------------------|--|
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A039b0 | |

Mil-std (military Standard):

Mil-g-45204 spec.

Shelf Life: