Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-408-6692

# **Body Style:**

Straight shape, external coupling

# **Overall Length:**

1.243 inches

# **Overall Diameter:**

2.312 inches

# Distance From Mounting Shoulder To Front Face:

0.599 inches

#### Mounting Facility Thickness:

Between 0.062 inches and 0.125 inches

# Threaded Device Type:

Back shell and mounting bushing

# Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

25-29 single mating end

# **Contact Removability:**

Removable single mating end single contact grouping

#### Shell Type:

Solid

# Connector Locking Method:

Bayonet pin

# **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping

#### **Insert Material:**

Plastic epoxy single mating end

#### **Terminal Type:**

Crimp single mating end single contact grouping

#### Shell Material:

Aluminum alloy

#### Shell Surface Treatment:

Cadmium

#### Included Contact Quantity:

29 single mating end single contact grouping

# Bushing Accommodation Hole Shape:

Round w/flat

#### Included Contact Type:

Round pin single mating end single contact grouping



#### Precious Material And Location:

Contact surfaces gold

#### **Precious Material:**

Gold

#### Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Specification Data:**

96906-ms27468 government standard

Shelf Life: N/a Unit Of Measure:

---

# Demilitarization:

No

Fiig:

A039b0

#### Mil-std (military Standard):

Mil-c-38999 spec.